



# Material Safety Data Sheet

TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazards Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

The following material safety data sheet covers the hazardous ingredients associated with more than one color aerosol spray pair. As per 29 CFR 1900.1200 paragraph (g) whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following AerVOE Pacific aerosol spray paint.

## ENGINE ENAMELS

510 CLEAR	530 CADILLAC GOLD	561 CHEVY BLUE	575 DULL ALUMINUM
511 UNIVERSAL WHITE	532 FORD GOLD	562 G.M. BLUE	580 CUMMINS BEIGE
512 FLAT BLACK	540 ALPINE GREEN	566 FORD-MERC BLUE	581 PONTIAC MET BLUE
513 SATIN BLCK	550 FORD RED	568 CHRYSLER BLUE	582 CAST IRON GRAY
514 GLOSS BLACK	551 FORD GRAY	570 UNIVERSAL SILVER	583 STEEL BLAST GRAY
520 CHEVY ORANGE	560 FORD BLUE		

PRODUCT NAME: (13A) ENGINE ENAMELS ALL COLORS

PRODUCT CODE: 13 A

HMIS CODES: H F R P  
 2 4 1

PRODUCT USE: ENGINE ENAMELS <80% V.O.C.

## SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: AerVOE-Pacific Company, Inc.

ADDRESS: 1198 Sawmill Rd., Gardnerville, NV 89410

EMERGENCY PHONE: 1-800-424-9300

DATE REVISED: 01-18-93

INFORMATION PHONE: (702) 782-0100

NAME OF PREPARER: Mike A. Traquina

REASON REVISED: Updated

## SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

### OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS/WEIGHT PERCENT	OSHA PEL	ACGIH TLV	OTHER	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
*SS 12 XYLENE (CAS 1330 20 7) 6	100PPM	100PPM		4300mg/kg RAT ORAL	6700PPM; 4hr RAT INHA.
*SS 41 ACETONE (CAS 67 64 1) 33	750 PPM	750 PPM		9750mg/kg RAT ORAL	N/A
PR 01A PROPANE (CAS 74 98 6) 20	1000 PPM	1000 PPM		N/A	N/A
PR 01B ISOBUTANE (CAS 75 28 5) <5.0%	800 PPM	800 PPM	<-ESTIMATE	N/A	520000 PPM; 2hr Mouse Exp
PR 01C NORMAL BUTANE (CAS 106 97 8) 10	600 PPM	600 PPM		N/A	658mg/L; 4hr RAT INHA.

\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

NOTE: N/A applies to not available or not applicable